

NOTES:

- 1. RESTORATION ON RESIDENTIAL ROADWAYS SHALL INCLUDE 4" ODOT ITEM 301 AND 2" OF ODOT ITEM 448.
 RESTORATION ON MAIN ROADWAYS SHALL INCLUDE 10" OF ODOT ITEM 301 AND 2" OF ODOT ITEM 441 (448).
- 2. ITEM 304 AGGREGATE BASE, COMPACTED, AS DIRECTED BY ENGINEER
- 3. 98% COMPACTED ODOT ITEM 310 OR FLOWABLE FILL (LSM 100)
- 4. AC SEAL EDGE TOP

- 5. REAT ALL EDGES WITH JOINT ADHESIVE (ODOT 401.14)
- 6. ITEM C407 TRACKLESS TACK COAT
- 7. FOR OPEN-CUTS IN THE ROADWAY, GRAVEL, ODOT ITEM 310, OR FLOWABLE FILL (LSM 100) BACKFILL IS REQUIRED.
- 8. IF BORING OR POTHOLING THE ROADWAY, BACKFILL WITH FLOWABLE FILL.



CITY OF
CENTERVILLE, OH
PUBLIC WORKS DEPARTMENT
7970 SOUTH SUBURBAN ROAD
CENTERVILLE, OHIO 45458
PHONE (937) 428–4782
FAX (937) 433–0286

ROADWAY / RIGHT-OF-WAY CUTS Approval:

James Brinegar
City Engineer

Date: June 2021 Revision:

Scale: Sheet: None _____ of ___1