



**NOTES:**

1. RESTORATION ON RESIDENTIAL ROADWAYS SHALL INCLUDE 4" ODOT ITEM 301 AND 2" OF ODOT ITEM 448. RESTORATION ON MAIN ROADWAYS SHALL INCLUDE 10" OF ODOT ITEM 301 AND 2" OF ODOT ITEM 441 (448).
2. ITEM 304 AGGREGATE BASE, COMPACTED, AS DIRECTED BY ENGINEER. 4" DEPTH ON RESIDENTIAL ROADWAYS AND 6" DEPTH ON MAIN ROADWAYS.

3. 98% COMPACTED ODOT ITEM 310 OR FLOWABLE FILL (LSM 100)
4. AC SEAL EDGE TOP
5. REAT ALL EDGES WITH JOINT ADHESIVE (ODOT 401.14)
6. ITEM C407 TRACKLESS TACK COAT
7. FOR OPEN-CUTS IN THE ROADWAY, GRAVEL, ODOT ITEM 310, OR FLOWABLE FILL (LSM 100) BACKFILL IS REQUIRED.
8. IF BORING OR POTHOLING THE ROADWAY, BACKFILL WITH FLOWABLE FILL.

	CITY OF CENTERVILLE, OH	ROADWAY / RIGHT-OF-WAY CUTS	Approval: _____	Date: June 2021		
	PUBLIC WORKS DEPARTMENT 7970 SOUTH SUBURBAN ROAD CENTERVILLE, OHIO 45458 PHONE (937) 428-4782 FAX (937) 433-0286		James Brinegar City Engineer		Revision:	
			Scale: None	Sheet: 1 of 1		