

## Item C660 - Sodding

- C660.1 Description**
- C660.2 Material and Construction**
- C660.3 Method of Measurement**
- C660.4 Basis of Payment**

**C660.1 Description.** This work shall consist of sodding areas in accordance with the requirements of ODOT Item 659 of the State of Ohio, Construction and Materials Specifications manual. Topsoil shall meet the requirements of ODOT Item 653.

**C660.2 Preparation.** Sub-grade preparations shall meet the requirements of section 660.04, except that all areas shall be free from rock or other foreign material of one (1) inch or greater in any dimension. Place 4" of topsoil according to Item C659.

**C660.3 General.** The Contractor shall complete all restoration work (backfill, topsoil, and sodding) within 2 weeks after the concrete work is completed on each street. The Contractor shall be responsible for the restoration until final acceptance of the project and shall repair or replace any damaged areas as directed by the City Engineer. The Contractor may be directed to perform additional sodding/seeding and mulching at the time the punch list items are completed. The sod furnished shall be well-rooted Kentucky Blue Grass containing a growth of not more than 30% of other grasses, and free from all noxious weeds and grasses. The Contractor shall be responsible to water the restored (seeded) area per the requirements of section 659.17.

**C660.4 Basis of Payment.**  
Payment will be based on the price bid:

<b>Item</b>	<b>Unit</b>	<b>Description</b>
C660	Each Ramp	Sodding including 4" Topsoil